

## **Technical Specification**

**Product Code: SHDV116R8TB** 

**Description:** HDview Analogue 4MP 16CH DVR 8TB





General Information		Recording	
Dimensions (mm) 380	x 340 x 50	Maximum Capacity	
Warranty (Years) 3			8 Terabytes per SATA connection
Supply & Power		0 7:	Internal HDD:8TB
Operating Voltage (V DC) 12		SATA Connection(s)	
Power Consumption (mA) <2		Recording Resolution	
Inputs & Outputs		Poording Mode	1080p @ 25 FPS (PAL)  Manual, Schedule, Alarm
Alarm Inputs 16		Environment	Mariual, Scriedule, Alaim
Alarm Outputs 1			
Video Input Channels (BNC) 16 (BNC Ports)		Operating Temperature	e (°C)   -10 to +50
Audio Input Channels (RCA) 4 (Or	nboard), 12 (Via DE-15 Socket)		
Audio Output Channels (RCA) 1			
Media Information			
Display Video Output	1 x HDMI, 1 x VGA, 1 x BNC		
	1, 4, 6, 8, 9, 10, 12, 13, 14, 16, 17, 19, 20, 22 & 25		
Display Resolutions HDMI: 1024x768, 1280			560x1440, 3840x2160/EDID
	VGA: 1024x768, 1280x720, 1280	0x1024, 1440x900, 1920x1080	
	BNC: 704x576		
	Sync Playback Maximum 16 Channels		
Backup Mode Network and USB2.0 (Up to 320		GB Storage Medium Supported)	
Hardware Reset Yes			
Network			
Interface	2 x USB, 1 x RS485		
Network Connection RJ45; 10/100 BASE-T			
Network Monitoring Mobile app, Windows & Mac Clien		ient, Web Interface	
	ower Supply, 1 x DE-15 Plug with hernet Cable (0.5m)	12 RCA Audio Connections, 1 x U	SB Mouse (0.5m), 1 x C13 IEC Cable
MON18L: 18 MON21L: 21. MON23L: 23.	e of Cameras	Pan, Tilt and Zoom (PTZ) Camera	
Additional Information Playback Fun Slow Forward	ction: Fast Forward & Reverse (2: (1/2x, 1/4x, 1/8x, 1/16x)	x, 4x, 8x, 16x)	

**Accessories Features** 

DVRPSU4: 12V DC 5 Amp Power Supply Unit Line Cross Detection HDVIP1632RRMB: Rack Mount Bracket Perimeter Intrusion Detection

CPS18W: 18 Way 12V DC 10 Amp CCTV Power Supply Premium Surveillance Hard Disk Drive Pre-installed Up-the-Coax (UTC) Protocol Supported









