Xnightsbridge

DATASHEET



12DC40

IP20 12V DC 40W LED Driver - Constant Voltage

www.mlaccessories.co.uk

NET WEIGHT (KG) 0.14 FINISH White DIMENSIONS (MM) Length - 166 Height - 24 Width - 52 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING IP20 DISPLACEMENT FACTOR >0.9 SVM 0 PST-LM 0 LIFE SPAN (HRS) 50,000 DIMMABLE No INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT OUTRAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Ta)20~50°C WARRANTY 1year(s)	MLA PART CODE	12DC40
FINISH White DIMENSIONS (MM) Length - 166 Height - 24 Width - 52 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING IP20 DISPLACEMENT FACTOR >0.9 SVM 0 PST-LM 0 LIFE SPAN (HRS) 50,000 DIMMABLE No INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE 12V DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT CUTRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 EFFICIENCY FULL LOAD - 85 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20-50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	DESCRIPTION	IP20 12V DC 40W LED Driver - Constant Voltage
DIMENSIONS (MM) Length - 166 Height - 24 Width - 52 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING DISPLACEMENT FACTOR SVM 0 PST-LM 0 LIFE SPAN (HRS) DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIVER DRIVER DRIVER DRIVER Life SPAN (HRS) DRIVER DRIVER DRIVER DRIVER DRIVER DRIVER Life SPAN (HRS) SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	NET WEIGHT (KG)	0.14
DIMENSIONS (MM) Height - 24 Width - 52 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING IP20 DISPLACEMENT FACTOR SVM 0 PST-LM 0 LIFE SPAN (HRS) DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIV	FINISH	White
I	DIMENSIONS (MM)	Height - 24
IP RATING DISPLACEMENT FACTOR SVM 0 PST-LM 0 LIFE SPAN (HRS) 50,000 DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DR	CONSTRUCTION	Construction - Polycarbonate
DISPLACEMENT FACTOR SVM 0 PST-LM 0 LIFE SPAN (HRS) 50,000 DIMMABLE NO INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	CLASS	II
PST-LM DIFF SPAN (HRS) DIMMABLE NO INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIVE	IP RATING	IP20
PST-LM LIFE SPAN (HRS) DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	DISPLACEMENT FACTOR	>0.9
LIFE SPAN (HRS) DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	SVM	0
DIMMABLE INDUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	PST-LM	0
INPUT VOLTAGE SECONDARY VOLTAGE 12V DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	LIFE SPAN (HRS)	50,000
DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 12V DRIVER DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT - 40W OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C	DIMMABLE	No
DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	INPUT VOLTAGE	230V 50Hz
MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C WARRANTY 1year(s)	SECONDARY VOLTAGE	12V
, , , , , , , , , , , , , , , , , , ,	DRIVER	MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C
MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493	WARRANTY	1year(s)
	MANUFACTURED IN ACCORDANCE WITH	EN 61347, EN 62493
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832991656	EAN	5055832991656

Date Created: 03/04/2023 13:18



