



## DATASHEET



### BATSCDA4

### 230V 4ft 32W DALI CCT Adjustable Batten

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	<b>BATSCDA4</b>
DESCRIPTION	230V 4ft 32W DALI CCT Adjustable Batten
NET WEIGHT (KG)	1.35
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	32
LAMP TECHNOLOGY	LED
LUMENS (LM)	3790/4480/4120
LUMENS LIGHT SOURCE ONLY (LM)	4970
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	157.16
CIRCUIT WATTAGE (W)	31.66
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.141
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	105
L70B50 LIFESPAN (HRS)	60,000
OPERATING TEMPERATURE	-20~40°C

<b>INPUT VOLTAGE</b>	230V 50Hz
<b>CABLE GLAND INCLUDED</b>	No
<b>DRIVER</b>	DRIVER TYPE - DALI MAX. OUTPUT - 31.5W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - up to 750mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 95 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
<b>STANDBY POWER</b>	≤ 0.5WW
<b>WARRANTY</b>	5year(s)
<b>ORIGIN OF MANUFACTURE</b>	China
<b>DECLARATION OF CONFORMITY (HELD ON FILE)</b>	Yes
<b>EAN</b>	5056270881707

Date Created: 03/04/2023 13:56

