Xnightsbridge


DATASHEET



BATSCDA6

230V 6ft 48W DALI CCT Adjustable Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCDA6
DESCRIPTION	230V 6ft 48W DALI CCT Adjustable Batten
NET WEIGHT (KG)	1.92
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1790 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	48
LAMP TECHNOLOGY	LED
LUMENS (LM)	6050/7040/6580
LUMENS LIGHT SOURCE ONLY (LM)	7820
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	161.05
CIRCUIT WATTAGE (W)	48.56
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.216
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	135
L70B50 LIFESPAN (HRS)	60,000
OPERATING TEMPERATURE	-20~40°C





Xnightsbridge

INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - DALI MAX. OUTPUT - 63W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - up to 1500mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 90.9 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881721

Date Created: 03/04/2023 13:56





