Xnightsbridge

DATASHEET




BATSCDAST5

230V 5ft 40W DALI CCT Adjustable Self-Test

Emergency Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCDAST5
DESCRIPTION	230V 5ft 40W DALI CCT Adjustable Self-Test Emergency Batten
NET WEIGHT (KG)	1.87
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1525 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	40
LAMP TECHNOLOGY	LED
LUMENS (LM)	4960/5720/5410
LUMENS LIGHT SOURCE ONLY (LM)	6330
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	157.82
LUMENS EMERGENCY MODE (LM)	360
CIRCUIT WATTAGE (W)	40.15
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.179
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	145
L70B50 LIFESPAN (HRS)	60,000





Xnightsbridge

EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	-5~40°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - DALI MAX. OUTPUT - 44.1W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - up to 1050mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 93 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
BATTERY INCLUDED	Yes
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881745

Date Created: 03/04/2023 13:56





