



## DATASHEET



### BATSCWST4

230V 4ft 18/32W CCT Adjustable Self-Test Emergency Batten

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	BATSCWST4
DESCRIPTION	230V 4ft 18/32W CCT Adjustable Self-Test Emergency Batten
NET WEIGHT (KG)	1.56
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	18/32
LAMP TECHNOLOGY	LED
LUMENS (LM)	2380/2600/2570, 3950/4490/4310
LUMENS LIGHT SOURCE ONLY (LM)	5020
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	159.14
LUMENS EMERGENCY MODE (LM)	320
CIRCUIT WATTAGE (W)	31.6
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.142
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	145
L70B50 LIFESPAN (HRS)	60,000

<b>DIMMABLE</b>	No
<b>EMERGENCY</b>	Maintained / Non-maintained / Switched
<b>SELF-TEST</b>	Yes
<b>OPERATING TEMPERATURE</b>	-5~50°C
<b>INPUT VOLTAGE</b>	230V 50Hz
<b>CABLE GLAND INCLUDED</b>	No
<b>DRIVER</b>	DRIVER TYPE - Constant Current MAX. OUTPUT - 16/31W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 360/720mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 97.1 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
<b>BATTERY INCLUDED</b>	Yes
<b>WARRANTY</b>	5year(s)
<b>WARRANTY INFORMATION</b>	(excluding battery)
<b>ORIGIN OF MANUFACTURE</b>	China
<b>DECLARATION OF CONFORMITY (HELD ON FILE)</b>	Yes
<b>EAN</b>	5056270881448

Date Created: 03/04/2023 13:56

