


DATASHEET



BF2440EMS

230V IP44 24W BF LED Emergency Bulkhead with Sensor 400mm 1600lm 6000K

www.mlaccessories.co.uk



| MLA PART CODE | BF2440EMS |
|-------------------------------|--|
| DESCRIPTION | 230V IP44 24W BF LED Emergency Bulkhead with Sensor 400mm 1600lm 6000K |
| NET WEIGHT (KG) | 1.7 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 388 Projection - 117 Base Diameter - 345 |
| CONSTRUCTION | Construction - Polycarbonate Construction 2 - & acrylic |
| CLASS | II |
| IP RATING | IP44 |
| WATTAGE (W) | 24 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1600 |
| LUMENS LIGHT SOURCE ONLY (LM) | 2425 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 68.2 |
| LUMENS EMERGENCY MODE (LM) | 277 |
| CIRCUIT WATTAGE (W) | 23.6 |
| CCT | 6000K |
| LIGHT COLOUR | Daylight |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.11 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0 |
| PST-LM | 0.021 |

| | |
|--|--|
| BEAM ANGLE (DEGREES) | 115 |
| LIFE SPAN (HRS) | 50,000 |
| L70B50 LIFESPAN (HRS) | 60,000 |
| DIMMABLE | No |
| EMERGENCY | Maintained / Non-maintained / Switched |
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| SENSOR TYPE | Microwave |
| SENSOR DETECTION ANGLE (DEGREES) | 360 |
| OPTIMUM DETECTION RANGE (M) | 2 - 8m |
| SENSOR DURATION | 3s - 30min |
| SENSOR LUX SETTINGS | 2 - 2000lx |
| BATTERY INCLUDED | Yes |
| STANDBY POWER | 0.08W |
| WARRANTY | 3year(s) |
| WARRANTY INFORMATION | (excluding battery) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055559190790 |

Date Created: 03/04/2023 14:18

