



DATASHEET



BT14ACTDALIEM

230V IP65 14W CCT Adjustable DALI LED
Emergency Bulkhead

www.mlaccessories.co.uk



MLA PART CODE	BT14ACTDALIEM
DESCRIPTION	230V IP65 14W CCT Adjustable DALI LED Emergency Bulkhead
NET WEIGHT (KG)	1.1
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 315 Projection - 74
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1230/1410/1375
LUMENS LIGHT SOURCE ONLY (LM)	1800/2000/1920
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	147
LUMENS EMERGENCY MODE (LM)	170
CIRCUIT WATTAGE (W)	13.6
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.062
DISPLACEMENT FACTOR	>0.9
BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes

EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270844405

Date Created: 19/08/2024 15:30

