Knightsbridge


DATASHEET



BT20ACTDALIEM

230V IP65 20W CCT Adjustable DALI LED Emergency Bulkhead

www.mlaccessories.co.uk



| MLA PART CODE | BT20ACTDALIEM |
|-------------------------------|---|
| DESCRIPTION | 230V IP65 20W CCT Adjustable DALI LED Emergency Bulkhead |
| NET WEIGHT (KG) | 1.5 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 380 Projection - 81 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | I |
| IP RATING | IP65 |
| IK RATING | IK08 |
| WATTAGE (W) | 20 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1820/2070/2010 |
| LUMENS LIGHT SOURCE ONLY (LM) | 2580/2740/2665 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 137.57 |
| LUMENS EMERGENCY MODE (LM) | 165 |
| CIRCUIT WATTAGE (W) | 19.9 |
| ССТ | 3000/4000/5700K |
| LIGHT COLOUR | ССТ |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.090 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.017 |
| PST-LM | 0.027 |
| BEAM ANGLE (DEGREES) | 115 |





Knightsbridge

| L70B50 LIFESPAN (HRS) | 50,000 |
|--|--|
| LED COMPATIBLE | Yes |
| EMERGENCY | Maintained / Non-maintained / Switched |
| OPERATING TEMPERATURE | -20~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Blind grommet |
| BATTERY INCLUDED | Yes |
| WARRANTY | 5year(s) |
| WARRANTY INFORMATION | (excluding battery) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270844443 |
| Data Created: 10/08/2024 15:28 | |

Date Created: 19/08/2024 15:28





