



DATASHEET



CBL15SS

230V IP65 15W Stainless Steel LED Bollard 950mm - 3000K

www.mlaccessories.co.uk



MLA PART CODE	CBL15SS
DESCRIPTION	230V IP65 15W Stainless Steel LED Bollard 950mm - 3000K
NET WEIGHT (KG)	8.8
FINISH	Stainless Steel
DIMENSIONS (MM)	Diameter - 160 Height - 950
CONSTRUCTION	Construction - 304 Stainless steel
CLASS	I
IP RATING	IP65
WATTAGE (W)	15
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	810
LUMENS LIGHT SOURCE ONLY (LM)	1930
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	130.65
CIRCUIT WATTAGE (W)	14.80
CCT	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.1401
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0.02
BEAM ANGLE (DEGREES)	360
L70B50 LIFESPAN (HRS)	45,000
LED COMPATIBLE	Yes
DIMMABLE	No

OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	1
CABLE TYPE	3 x 1.0sq mm H05RN-F
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 16.8W OUTPUT VOLTAGE - 12-48V OUTPUT CURRENT - 350mA EFFICIENCY FULL LOAD - 84 AMBIENT TEMPERATURE (Ta) - -30~70°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270873641

Date Created: 03/04/2023 13:52

