


DATASHEET



CBL26BK

230V IP65 26W IK08 LED Bollard 1000mm - 3000K

www.mlaccessories.co.uk



MLA PART CODE	CBL26BK
DESCRIPTION	230V IP65 26W IK08 LED Bollard 1000mm - 3000K
NET WEIGHT (KG)	10.6
FINISH	Matt Black
DIMENSIONS (MM)	Diameter - 200 Height - 1000
CONSTRUCTION	Construction - Die-cast aluminium Construction 2 - & stainless steel
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	26
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	650
LUMENS LIGHT SOURCE ONLY (LM)	3645
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	136.54
CIRCUIT WATTAGE (W)	26.69
CCT	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.1228
DISPLACEMENT FACTOR	>0.9
SVM	1.09
PST-LM	0.04
BEAM ANGLE (DEGREES)	360
L70B50 LIFESPAN (HRS)	45,000
LED COMPATIBLE	Yes

DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	1
CABLE TYPE	3 x 1.0sq mm H05RN-F
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30.1W OUTPUT VOLTAGE - up to 60V OUTPUT CURRENT - 700mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 91 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 80°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270873634

Date Created: 03/04/2023 13:52

