Knightsbridge

DATASHEET



CS9909BC

13A 2G DP switched socket with dual USB A + C (FASTCHARGE) - Brushed chrome with black insert

www.mlaccessories.co.uk

(PASICHARGE) - Brushed Chrome with black firsentNET WEIGHT (KG)0.271FINISHBrushed ChromeINSERT COLOURBlackDIMENSIONS (MM)Height - 89 Width - 149.3 Projection - 10.5MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASS1IP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF TYPE-A PORTS1NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGINGSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	MLA PART CODE	CS9909BC
FINISHBrushed ChromeINSERT COLOURBlackDIMENSIONS (MM)Height - 89 Width - 149.3 Projection - 10.5MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	DESCRIPTION	
INSERT COLOURBlackDIMENSIONS (MM)Height - 89 Width - 149.3 Projection - 10.5MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF TYPE-A PORTS1NO. OF TYPE-A PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesWARRANTY2year(s)	NET WEIGHT (KG)	0.271
DIMENSIONS (MM)Height - 89 Width - 149.3 Projection - 10.5MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2A/ With QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	FINISH	Brushed Chrome
DIMENSIONS (MM)Width - 149.3 Projection - 10.5MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesWARRANTY2year(s)	INSERT COLOUR	Black
CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	DIMENSIONS (MM)	Width - 149.3
CLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
IP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	CONSTRUCTION	Construction - Premium grade steel
INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	CLASS	I
SWITCH TYPEDouble PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	IP RATING	IP20
EARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD13ATERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	SWITCH TYPE	Double Pole
TERMINAL TYPECaptiveTERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	EARTH TERMINAL	Yes
TERMINAL CAPACITY $2 \times 2.5 \text{mm}^2 \text{ or } 1 \times 4.0 \text{mm}^2$ NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	LOAD/MAX. LOAD	13A
NO. OF USB PORTS2NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	TERMINAL TYPE	Captive
NO. OF TYPE-A PORTS1NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	TERMINAL CAPACITY	2 x 2.5mm ² or 1 x 4.0mm ²
NO. OF TYPE-C PORTS1USB CHARGING5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2AADDITIONAL FEATURESSwitches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devicesFUNCTIONBoth ports can operate as FASTCHARGE but not at the same timeWARRANTY2year(s)	NO. OF USB PORTS	2
USB CHARGING 5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2A ADDITIONAL FEATURES Switches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devices FUNCTION Both ports can operate as FASTCHARGE but not at the same time WARRANTY 2year(s)	NO. OF TYPE-A PORTS	1
OSB CHARGING Type-A USB Outlet max. 2A ADDITIONAL FEATURES Switches Voltage from standard 5V up to 12V Max. 20W output with QC2.0 compliant devices FUNCTION Both ports can operate as FASTCHARGE but not at the same time WARRANTY 2year(s)	NO. OF TYPE-C PORTS	1
ADDITIONAL FEATORES with QC2.0 compliant devices FUNCTION Both ports can operate as FASTCHARGE but not at the same time WARRANTY 2year(s)	USB CHARGING	5V-12V DC 4.0A FASTCHARGE Type-C USB Outlet max. 3A / Type-A USB Outlet max. 2A
WARRANTY 2year(s)	ADDITIONAL FEATURES	
	FUNCTION	
MANUFACTURED IN ACCORDANCE WITH BS1363-2, EN 62368-1, EN 62680-1-1	WARRANTY	2year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS1363-2, EN 62368-1, EN 62680-1-1
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China





Knightsbridge

DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270807059

Date Created: 03/04/2023 14:20







ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.