Xnightsbridge

DATASHEET



CU9RCD

13A 2G DP RCD Switched Socket - 30mA (Type A)

www.mlaccessories.co.uk

MLA PART CODE	CU9RCD
DESCRIPTION	13A 2G DP RCD Switched Socket - 30mA (Type A)
NET WEIGHT (KG)	0.237
FINISH	White
DIMENSIONS (MM)	Height - 86 Width - 146 Projection - 10
MINIMUM MOUNTING BOX DEPTH	35mm
CONSTRUCTION	Construction - Thermoset resin
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	3 x 2.5mm² or 2 x 4.0mm²
FUNCTION	RCD trip current of 30mA. Latching type RCD. RCD trip speed of less than 40ms
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, BS 7288
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811490

Date Created: 03/04/2023 13:29





