## Knightsbridge

## DATASHEET



## **EMLED4L**

230V IP65 3W LED Emergency Bulkhead Maintained/Non- Maintained

www.mlaccessories.co.uk

DESCRIPTION2NET WEIGHT (KG)7FINISH7DIFFUSER7DIMENSIONS (MM)7CONSTRUCTION7CLASS7IP RATING7WATTAGE (W)7LAMP TECHNOLOGY7LAMP INCLUDED7	30V IP65 3W LED Emergency Bulkhead Maintained/Non- Maintained 0.5 White Prismatic Length - 350 Width - 117 Projection - 60 Construction - Polycarbonate II IP65
FINISH         DIFFUSER         DIMENSIONS (MM)         CONSTRUCTION         CLASS         IP RATING         WATTAGE (W)         LAMP TECHNOLOGY	White         Prismatic         Length - 350         Width - 117         Projection - 60         Construction - Polycarbonate         II         IP65
DIFFUSER DIMENSIONS (MM) CONSTRUCTION CLASS IP RATING WATTAGE (W) LAMP TECHNOLOGY	Prismatic Length - 350 Width - 117 Projection - 60 Construction - Polycarbonate II IP65
DIMENSIONS (MM) CONSTRUCTION CLASS IP RATING WATTAGE (W) LAMP TECHNOLOGY	Length - 350 Width - 117 Projection - 60 Construction - Polycarbonate II IP65
CONSTRUCTION CLASS IP RATING WATTAGE (W) LAMP TECHNOLOGY	Width - 117 Projection - 60 Construction - Polycarbonate II IP65
CLASS IP RATING WATTAGE (W) LAMP TECHNOLOGY	II IP65
IP RATING WATTAGE (W) LAMP TECHNOLOGY	IP65
WATTAGE (W) LAMP TECHNOLOGY	
LAMP TECHNOLOGY	
	3
LAMP INCLUDED	SMD LED
	Yes
LUMENS (LM)	125
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	43.71
LUMENS EMERGENCY MODE (LM)	125
CIRCUIT WATTAGE (W)	2.9
ССТ	5500K
LIGHT COLOUR	Daylight
CRI	>80
RUNNING CURRENT (A)	0.026
SVM	0.02
LIFE SPAN (HRS)	25,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No
OPERATING TEMPERATURE	0~45°C





## Knightsbridge

INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	2 x 20
CABLE GLAND INCLUDED	Blind grommet
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270880823

Date Created: 16/10/2023 15:00





