Xnightsbridge

DATASHEET



EMPOWERW2

230V IP20 3W LED Emergency Downlight 3000K (maintained/non-maintained)

www.mlaccessories.co.uk

MLA PART CODE	EMPOWERW2
DESCRIPTION	230V IP20 3W LED Emergency Downlight 3000K (maintained/non-maintained)
NET WEIGHT (KG)	0.39
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 55 Height - 32 Recessed Depth - 30 Minimum Void - 80
CUT-OUT (MM)	Cut-out Diameter - 46
CONSTRUCTION	Construction - Die-cast aluminium Construction 2 - & polycarbonate
CLASS	ll l
IP RATING	IP20
WATTAGE (W)	3
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	145
LUMEN TOLERANCE	5%
LUMENS EMERGENCY MODE (LM)	145
CIRCUIT WATTAGE (W)	5.4
ССТ	3000K
LIGHT COLOUR	Warm White
RUNNING CURRENT (A)	0.047
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No
IC RATED	No





Xnightsbridge

OPERATING TEMPERATURE	0~45°C
INPUT VOLTAGE	230V 50Hz
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598-2-22
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832931522

Date Created: 03/04/2023 12:50





