Xnightsbridge


DATASHEET



FLN50

230V IP65 50W LED FLOOD

www.mlaccessories.co.uk



E

MLA PART CODE	FLN50
DESCRIPTION	230V IP65 50W LED FLOOD
NET WEIGHT (KG)	0.589
FINISH	Black
DIFFUSER	Clear
DIMENSIONS (MM)	Height - 177 Width - 200 Depth - 28 Projection - 180 Overall Height - 245
CONSTRUCTION	Construction - Die-cast aluminium Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	50
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	5430
LUMENS LIGHT SOURCE ONLY (LM)	6050
LUMEN TOLERANCE	10%
EFFICACY (LM/W)	125.84
CIRCUIT WATTAGE (W)	48.08
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.213
DISPLACEMENT FACTOR	>0.9
SVM	0.032
PST-LM	0.082
BEAM ANGLE (DEGREES)	105





Xnightsbridge

LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	Compression gland
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811100

Date Created: 03/04/2023 13:29





