Knightsbridge

DATASHEET



FP5APC

Flat Plate 5A unswitched socket - polished chrome with black insert

www.mlaccessories.co.uk

DESCRIPTIONFlat Plate 5A unswitched socket - polished chrome with black insertNET WEIGHT (KG)0.08FINISHPolished ChromeINSERT COLOURBlackDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelIP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	MLA PART CODE	FP5APC
FINISHPolished ChromeINSERT COLOURBlackDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelIP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	DESCRIPTION	Flat Plate 5A unswitched socket - polished chrome with black insert
INSERT COLOURBlackDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelIP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTYBS 546ORIGIN OF MANUFACTURED IN ACCORDANCE WITHChina	NET WEIGHT (KG)	0.08
DIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelIP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTYS546ORIGIN OF MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	FINISH	Polished Chrome
DIMENSIONS (MM)Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelIP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTYBS 546ORIGIN OF MANUFACTUREChina	INSERT COLOUR	Black
CONSTRUCTIONConstruction - Premium grade steelIP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	DIMENSIONS (MM)	Width - 87.5
IP RATINGIP20INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	MINIMUM MOUNTING BOX DEPTH	25mm
INPUT VOLTAGE230V 50HzEARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	CONSTRUCTION	Construction - Premium grade steel
EARTH TERMINALYesLOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	IP RATING	IP20
LOAD/MAX. LOAD5ATERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	INPUT VOLTAGE	230V 50Hz
TERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	EARTH TERMINAL	Yes
WARRANTY25year(s)MANUFACTURED IN ACCORDANCE WITHBS 546ORIGIN OF MANUFACTUREChina	LOAD/MAX. LOAD	5A
MANUFACTURED IN ACCORDANCE WITH BS 546 ORIGIN OF MANUFACTURE China	TERMINAL CAPACITY	2 x 1.0mm ² or 2 x 1.5mm ²
ORIGIN OF MANUFACTURE China	WARRANTY	25year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS 546
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	ORIGIN OF MANUFACTURE	China
	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832922087	EAN	5055832922087

Date Created: 03/04/2023 14:12

ACCESSORIES LTD



