Xnightsbridge

DATASHEET



GDM007BC

20AX 2 way SP key module (marked EMG LTG TEST) - brushed chrome

www.mlaccessories.co.uk

| DESCRIPTION20AX 2 way SP key module (marked EMG LTG TEST) - brushed chromeNET WEIGHT (KG)0.023FINISHBrushed ChromeDIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 2.5 Recessed Depth - 17.3MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION2-Way Key |
|--|
| FINISHBrushed ChromeDIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 2.5 Recessed Depth - 17.3MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle Pole |
| DIMENSIONS (MM) Height - 56.3 Width - 24.8 Projection - 2.5 Recessed Depth - 17.3 MINIMUM MOUNTING BOX DEPTH 35mm Construction - ABS Construction 2 - & steel IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole |
| DIMENSIONS (MM) Width - 24.8 Projection - 2.5 Recessed Depth - 17.3 MINIMUM MOUNTING BOX DEPTH 35mm CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole |
| CONSTRUCTION Construction - ABS Construction 2 - & steel IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole |
| CONSTRUCTION Construction 2 - & steel IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole |
| INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole |
| SWITCH TYPE Single Pole |
| <u> </u> |
| SWITCH FUNCTION 2-Way Key |
| |
| LOAD/MAX. LOAD 20AX |
| TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² |
| ADDITIONAL FEATURES Secret Key |
| WARRANTY 25year(s) |
| MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1 |
| ORIGIN OF MANUFACTURE China |
| DECLARATION OF CONFORMITY (HELD ON FILE) Yes |
| EAN 5055832963677 |

Date Created: 03/04/2023 13:03





