Knightsbridge

DATASHEET



GDM010BC

20AX DP key module - brushed chrome

www.mlaccessories.co.uk

DESCRIPTION20AX DP key module - brushed chromeNET WEIGHT (KG)0.023FINISHBrushed ChromeDIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 2.5 Recessed Depth - 17.3MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY0 5 pear(s)	A PART CODE	GDM010BC
FINISHBrushed ChromeDIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 2.5 Recessed Depth - 17.3MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	SCRIPTION	20AX DP key module - brushed chrome
DIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 2.5 Recessed Depth - 17.3MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	T WEIGHT (KG)	0.023
DIMENSIONS (MM)Width - 24.8 Projection - 2.5 Recessed Depth - 17.3MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	NISH	Brushed Chrome
CONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	MENSIONS (MM)	Width - 24.8 Projection - 2.5
CONSTRUCTIONConstruction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	NIMUM MOUNTING BOX DEPTH	35mm
INPUT VOLTAGE230V 50HzSWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	ONSTRUCTION	
SWITCH TYPEDouble PoleSWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	RATING	IP20
SWITCH FUNCTION1-Way KeyLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	PUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²ADDITIONAL FEATURESSecret KeyWARRANTY25year(s)	ИТСН ТҮРЕ	Double Pole
TERMINAL CAPACITY $3 \times 2.5 \text{mm}^2 \text{ or } 2 \times 4.0 \text{mm}^2$ ADDITIONAL FEATURESSecret KeyWARRANTY $25 \text{year}(s)$	VITCH FUNCTION	1-Way Key
ADDITIONAL FEATURES Secret Key WARRANTY 25year(s)	AD/MAX. LOAD	20AX
WARRANTY 25year(s)	RMINAL CAPACITY	3 x 2.5mm ² or 2 x 4.0mm ²
	DITIONAL FEATURES	Secret Key
	ARRANTY	25year(s)
MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	ANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1
ORIGIN OF MANUFACTURE China		China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	CLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832963790	N	5055832963790

Date Created: 03/04/2023 13:03





