Xnightsbridge


DATASHEET



KA6CWTD

KARA 230V IP20 6W LED Dimmable Recessed Panel - 4000K

www.mlaccessories.co.uk



MLA PART CODE	KA6CWTD
DESCRIPTION	KARA 230V IP20 6W LED Dimmable Recessed Panel - 4000K
NET WEIGHT (KG)	0.246
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 149 Base Diameter - 133 Recessed Depth - 24 Minimum Void - 75
CUT-OUT (MM)	Cut-out Diameter - 135
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	6
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	550
LUMENS LIGHT SOURCE ONLY (LM)	765
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	124.17
CIRCUIT WATTAGE (W)	6.16
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.037
SVM	0.023
PST-LM	0.094
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	30,000





Xnightsbridge

L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	Yes*
EMERGENCY CONVERSION KIT	EMKIT2
IC RATED	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 6W OUTPUT VOLTAGE - 27-42V OUTPUT CURRENT - 130mA POWER FACTOR - 0.5 AMBIENT TEMPERATURE (Ta) - 40°C CASE TEMPERATURE (Tc) - 70°C
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270842685

Date Created: 19/08/2024 15:30





