


DATASHEET



LEDGL3D

230V IP65 3W LED Stainless Steel Recessed Ground Light - 6000K

www.mlaccessories.co.uk



MLA PART CODE	LEDGL3D
DESCRIPTION	230V IP65 3W LED Stainless Steel Recessed Ground Light - 6000K
NET WEIGHT (KG)	0.451
FINISH	Stainless Steel
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 92 Projection - 3 Overall Height - 97 Recessed Depth - 94
CUT-OUT (MM)	Cut-out Diameter - 78 Cut-out with Sleeve - 78
CONSTRUCTION	Construction - 304 Stainless steel
CLASS	I
IP RATING	IP65
WATTAGE (W)	3
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	290
LUMENS LIGHT SOURCE ONLY (LM)	300
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	76.33
CIRCUIT WATTAGE (W)	3.97
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.039
DISPLACEMENT FACTOR	>0.9
SVM	0.035
PST-LM	0.88

BEAM ANGLE (DEGREES)	45
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
MAX. WEIGHT LOADING	800kg at 5mph
OPERATING TEMPERATURE	35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	2
CABLE TYPE	H05RN-F 3x0.75mm ²
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832938590

Date Created: 03/04/2023 12:54

