



DATASHEET



LFX512DL

12V IP20 LED Flex Daylight 6000K (5 metres)

www.mlaccessories.co.uk



MLA PART CODE	LFX512DL
DESCRIPTION	12V IP20 LED Flex Daylight 6000K (5 metres)
NET WEIGHT (KG)	0.072
DIMENSIONS (MM)	Length - 5300 Width - 8 Projection - 1.2
CLASS	III
IP RATING	IP20
WATTAGE (W)	4.8
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	520
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	113.9
CIRCUIT WATTAGE (W)	4.5
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
SDCM	<6
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	35,000
L70B50 LIFESPAN (HRS)	54,000
DIMMABLE	Driver dependent
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	12V DC
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270822113

