Xnightsbridge

DATASHEET




LUMI6060PRODALI

230V IP40 600 x 600mm CCT 30W LED Backlit DALI2

Panel

www.mlaccessories.co.uk



| MLA PART CODE | LUMI6060PRODALI |
|-------------------------------|--|
| DESCRIPTION | 230V IP40 600 x 600mm CCT 30W LED Backlit DALI2 Panel |
| NET WEIGHT (KG) | 1.9 |
| FINISH | White |
| DIFFUSER | Prismatic |
| DIMENSIONS (MM) | Length - 595 Height - 25 Width - 595 Projection - 9 |
| CONSTRUCTION | Construction - Aluminium |
| CLASS | II |
| IP RATING | IP40 |
| WATTAGE (W) | 30 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 3940/4100/3945 |
| LUMENS LIGHT SOURCE ONLY (LM) | 4530/4800/4800 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 123/134/124 |
| CIRCUIT WATTAGE (W) | 30.5 |
| ССТ | 3000/4000/5700K |
| LIGHT COLOUR | ССТ |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.13 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.01 |
| PST-LM | 0.01 |
| BEAM ANGLE (DEGREES) | 90 |
| L70B50 LIFESPAN (HRS) | 50000 |





Xnightsbridge

| EMERGENCY CONVERSION KIT | EMKIT2 |
|--|---------------|
| IC RATED | No |
| DIFFUSER RATING | TP(a) |
| OPERATING TEMPERATURE | -10~40°C |
| INPUT VOLTAGE | 230V 50Hz |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270867428 |

Date Created: 19/08/2024 15:30





