
Xnightsbridge


DATASHEET



ML500

230V IP44 500mm LED Circular Bathroom Mirror

www.mlaccessories.co.uk



MLA PART CODE	ML500
DESCRIPTION	230V IP44 500mm LED Circular Bathroom Mirror
NET WEIGHT (KG)	4.55
DIMENSIONS (MM)	Diameter - 500 Projection - 50 Base Diameter - 435 Base Depth - 45
CONSTRUCTION	Construction - Pressed steel Construction 2 - & glass
CLASS	I
IP RATING	IP44
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	55
LUMENS LIGHT SOURCE ONLY (LM)	1320
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	98.19
CIRCUIT WATTAGE (W)	13.47
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.034
PST-LM	0.003
LIFE SPAN (HRS)	20,000
L70B50 LIFESPAN (HRS)	30,000
LED COMPATIBLE	Yes





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 12W OUTPUT VOLTAGE - 25-40V OUTPUT CURRENT - 300mA POWER FACTOR - 0.82 EFFICIENCY FULL LOAD - 80 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
SENSOR TYPE	PIR
SENSOR OVERRIDE	No
OPTIMUM DETECTION RANGE (M)	0.030
STANDBY POWER	0.5W
WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270821611

Date Created: 03/04/2023 13:37





