


DATASHEET



MRBLED

230V IP20 32W LED CAT2 Recessed Modular Fitting
600x600mm 4000K

www.mlaccessories.co.uk



| MLA PART CODE | MRBLED |
|-------------------------------|--|
| DESCRIPTION | 230V IP20 32W LED CAT2 Recessed Modular Fitting 600x600mm 4000K |
| NET WEIGHT (KG) | 3.145 |
| FINISH | White |
| DIFFUSER | Clear |
| DIMENSIONS (MM) | Length - 595 Width - 595 Depth - 52 Recessed Depth - 52 |
| CONSTRUCTION | Construction - Steel |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 32 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 3370 |
| LUMENS LIGHT SOURCE ONLY (LM) | 3805 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 114.756 |
| CIRCUIT WATTAGE (W) | 33.2 |
| CCT | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.153 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.849 |
| PST-LM | 0.04 |
| BEAM ANGLE (DEGREES) | 105 |

| | |
|--|---|
| LIFE SPAN (HRS) | 30,000 |
| L70B50 LIFESPAN (HRS) | 50,000 |
| DIMMABLE | No |
| EMERGENCY CONVERSION KIT | EMKIT2 |
| IC RATED | No |
| OPERATING TEMPERATURE | -20~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 45W OUTPUT CURRENT - 1050mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 91 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 70°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055832931652 |

Date Created: 03/04/2023 12:51

