## **Knightsbridge**




## **NETRLBK**





www.mlaccessories.co.uk



NET WEIGHT (KG)0.174FINISHBlackDIMENSIONS (MM)Height - 50 Width - 50 Projection - 372 Recessed Depth - 33MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - Aluminium Construction 2 - & polycarbonateCLASSIIIP RATINGIP20WATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LMW)37.5CIRCUIT WATTAGE (W)1.9CCT30000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120LIMMABLENo	MLA PART CODE	NETRLBK
FINISHBlackDIMENSIONS (MM)Height - 50 Width - 50 Projection - 372 Recessed Depth - 33MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - Aluminium Construction - Aluminium Con	DESCRIPTION	Modular Reading Light 50 x 50mm - Black
Height - 50 Width - 50 Projection - 372 Recessed Depth - 33MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - Aluminium Construction 2 - & polycarbonateCLASSIIIP RATINGIP20WATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM120LTMS120LIMMABLENo	NET WEIGHT (KG)	0.174
DIMENSIONS (MM)Width - 50 Projection - 372 Recessed Depth - 33MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - Aluminium Construction 2 - & polycarbonateCLASSIIIP RATINGIIWATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70CTC3000KLIGHT COLOURWarm WhiteCRI-80RUNNING CURRENT (A)0.019SVM0.03Projection - 310120LIMENS LIGHT SOURCE ONLY (LM)0.019CT3000KLIGHT COLOURWarm WhiteCRI-80RUNNING CURRENT (A)0.019SVM0.03PST-LM120LTOB50 LIFESPAN (HRS)30,000DIMMABLENo	FINISH	Black
CONSTRUCTIONConstruction - Aluminium Construction 2 - & polycarbonateCLASSIIIP RATINGIP20WATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	DIMENSIONS (MM)	Width - 50 Projection - 372
CONSTRUCTIONConstruction 2 - & polycarbonateCLASSIIIP RATINGIP20WATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120LIMMABLENo	MINIMUM MOUNTING BOX DEPTH	35mm
IP RATINGIP20WATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120LIMMABLENo	CONSTRUCTION	
WATTAGE (W)2LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120LIMMABLENo	CLASS	II
LAMP TECHNOLOGYLEDLUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120LIOB50 LIFESPAN (HRS)30,000DIMMABLENo	IP RATING	IP20
LUMENS (LM)55LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120LTOB50 LIFESPAN (HRS)30,000DIMMABLENo	WATTAGE (W)	2
LUMENS LIGHT SOURCE ONLY (LM)70LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	LAMP TECHNOLOGY	LED
LUMEN TOLERANCE5%EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	LUMENS (LM)	55
EFFICACY (LM/W)37.5CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	LUMENS LIGHT SOURCE ONLY (LM)	70
CIRCUIT WATTAGE (W)1.9CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1	LUMEN TOLERANCE	5%
CCT3000KLIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	EFFICACY (LM/W)	37.5
LIGHT COLOURWarm WhiteCRI>80RUNNING CURRENT (A)0.019SVM0.03PST-LM<1BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	CIRCUIT WATTAGE (W)	1.9
CRI >80   RUNNING CURRENT (A) 0.019   SVM 0.03   PST-LM <1   BEAM ANGLE (DEGREES) 120   L70B50 LIFESPAN (HRS) 30,000   DIMMABLE No	сст	3000K
RUNNING CURRENT (A) 0.019   SVM 0.03   PST-LM <1   BEAM ANGLE (DEGREES) 120   L70B50 LIFESPAN (HRS) 30,000   DIMMABLE No	LIGHT COLOUR	Warm White
SVM 0.03   PST-LM <1   BEAM ANGLE (DEGREES) 120   L70B50 LIFESPAN (HRS) 30,000   DIMMABLE No	CRI	>80
PST-LM<1BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	RUNNING CURRENT (A)	0.019
BEAM ANGLE (DEGREES)120L70B50 LIFESPAN (HRS)30,000DIMMABLENo	SVM	0.03
L70B50 LIFESPAN (HRS) 30,000 DIMMABLE No	PST-LM	<1
DIMMABLE No	BEAM ANGLE (DEGREES)	120
	L70B50 LIFESPAN (HRS)	30,000
OPERATING TEMPERATURE 5~35°C	DIMMABLE	No
	OPERATING TEMPERATURE	5~35°C



## Knightsbridge

INPUT VOLTAGE	230V 50Hz
TERMINAL CAPACITY	2 x 1.0mm <sup>2</sup> or 2 x 1.5mm <sup>2</sup>
DRIVER	EFFICIENCY FULL LOAD - 0.63
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811797

Date Created: 16/10/2023 14:54





