

## DATASHEET



### PM6RCD

13A RCD fused spur (Type A) [Part M Compliant]

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)

MLA PART CODE	<b>PM6RCD</b>
DESCRIPTION	13A RCD fused spur (Type A) [Part M Compliant]
NET WEIGHT (KG)	0.155
FINISH	Anthracite
DIMENSIONS (MM)	Height - 86 Width - 86 Projection - 12
MINIMUM MOUNTING BOX DEPTH	35mm
CONSTRUCTION	Construction - Thermoset resin
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	2 x 2.5mm <sup>2</sup> or 1 x 4.0mm <sup>2</sup>
ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
FUNCTION	RCD trip current of 30mA. Latching type RCD. Cable outlet at bottom with strain relief. RCD trip speed of less than 40ms
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-4, BS 7288
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270887525

Date Created: 03/04/2023 14:11

