Xnightsbridge


DATASHEET




RW6CCT

230V IP65 6W Fire-rated LED CCT Adjustable Downlight

www.mlaccessories.co.uk





| MLA PART CODE | RW6CCT |
|-------------------------------|---|
| DESCRIPTION | 230V IP65 6W Fire-rated LED CCT Adjustable Downlight |
| NET WEIGHT (KG) | 0.218 |
| FINISH | White |
| DIFFUSER | Clear |
| DIMENSIONS (MM) | Diameter - 85 Projection - 7 Overall Height - 74 Recessed Depth - 67 Minimum Void - 120 |
| CUT-OUT (MM) | Cut-out Diameter - 72 |
| CONSTRUCTION | Construction - Aluminium Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP65 (IP20 from above) |
| WATTAGE (W) | 6 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 695 |
| LUMENS LIGHT SOURCE ONLY (LM) | 830 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 150.4 |
| CIRCUIT WATTAGE (W) | 5.56 |
| ССТ | 3000/4000/5000K |
| LIGHT COLOUR | ССТ |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.026 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.28 |
| PST-LM | 0.1 |





Xnightsbridge

| BEAM ANGLE (DEGREES) | 40 |
|--|-----------------------------|
| LIFE SPAN (HRS) | 40,000 |
| L70B50 LIFESPAN (HRS) | 54,000 |
| DIMMABLE | Yes* |
| FIRE-RATED | Tested to 30/60/90 minutes |
| IC RATED | Yes |
| OPERATING TEMPERATURE | 35°C |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | EFFICIENCY FULL LOAD - 80.6 |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055832981947 |

Date Created: 03/04/2023 13:13





