


DATASHEET



SA3040CDALI

SARA 230V IP20 LED Recessed Tri-Wattage and CCT DALI Scoop Downlight - 30/ 35/ 40W

www.mlaccessories.co.uk



| | |
|-------------------------------|--|
| MLA PART CODE | SA3040CDALI |
| DESCRIPTION | SARA 230V IP20 LED Recessed Tri-Wattage and CCT DALI Scoop Downlight - 30/ 35/ 40W |
| NET WEIGHT (KG) | 1.54 |
| FINISH | White |
| DIFFUSER | Clear |
| DIMENSIONS (MM) | Diameter - 190 Depth - 130 Minimum Void - 180 |
| CUT-OUT (MM) | Cut-out Diameter - 170 |
| TILT (DEGREES) | 40 |
| ROTATION (DEGREES) | 350 |
| CONSTRUCTION | Construction - Aluminium Construction 2 - & glass |
| CLASS | II |
| IP RATING | IP20 |
| WATTAGE (W) | 30 / 35 / 40 |
| LAMP TECHNOLOGY | CoB LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 3175/3505/3470, 3560/3940/3880, 3925/4415/4280 |
| LUMENS LIGHT SOURCE ONLY (LM) | 4975 |
| LUMEN TOLERANCE | 10% |
| EFFICACY (LM/W) | 130.48 |
| CIRCUIT WATTAGE (W) | 38.14 |
| CCT | 3000/4000/5000K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.168 |
| DISPLACEMENT FACTOR | >0.7 |

| | |
|--|--|
| SVM | 0.011 |
| PST-LM | 0.575 |
| BEAM ANGLE (DEGREES) | 38 |
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |
| EMERGENCY CONVERSION KIT | EMKIT2 |
| IC RATED | No |
| OPERATING TEMPERATURE | -25~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 45W OUTPUT VOLTAGE - 25-70V OUTPUT CURRENT - 350/500/600/700/800/900/1050mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 85°C |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270846393 |

Date Created: 19/08/2024 15:28

