



DATASHEET



SA3040RWAD

SARA 230V IP20 LED Recessed Tri-Wattage and CCT 0-10V Wallwasher - 30/ 35/ 40W

www.mlaccessories.co.uk



| | |
|-------------------------------|--|
| MLA PART CODE | SA3040RWAD |
| DESCRIPTION | SARA 230V IP20 LED Recessed Tri-Wattage and CCT 0-10V Wallwasher - 30/ 35/ 40W |
| NET WEIGHT (KG) | 1.57 |
| FINISH | White |
| DIFFUSER | Frosted |
| DIMENSIONS (MM) | Length - 157 Width - 240 Depth - 92 Minimum Void - 145 |
| CUT-OUT (MM) | Cut-out Box W/H/D - 225x127 |
| TILT (DEGREES) | 60 |
| CONSTRUCTION | Construction - Aluminium Construction 2 - & glass |
| CLASS | II |
| IP RATING | IP20 |
| WATTAGE (W) | 30 / 35 / 40 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 3795/4050/4175, 4240/4565/4680, 4760/5100/5235 |
| LUMENS LIGHT SOURCE ONLY (LM) | 5425 |
| LUMEN TOLERANCE | 10% |
| EFFICACY (LM/W) | 166.16 |
| CIRCUIT WATTAGE (W) | 35.96 |
| CCT | 3000/4000/5000K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.161 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0.013 |

| | |
|--|---|
| PST-LM | 0.575 |
| BEAM ANGLE (DEGREES) | 80 |
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | Yes* |
| EMERGENCY CONVERSION KIT | EMKIT2 |
| IC RATED | No |
| OPERATING TEMPERATURE | -25~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 9-42V OUTPUT CURRENT - 1000mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87 AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270845556 |

Date Created: 19/08/2024 15:28

