



DATASHEET



SER1525DALI

SEREN 230V IP40 LED Recessed Tri-Wattage and CCT DALI Downlight - 15/ 20/ 25W

www.mlaccessories.co.uk



MLA PART CODE	SER1525DALI
DESCRIPTION	SEREN 230V IP40 LED Recessed Tri-Wattage and CCT DALI Downlight - 15/ 20/ 25W
NET WEIGHT (KG)	0.97
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 192 Recessed Depth - 69.5 Minimum Void - 100
CUT-OUT (MM)	Cut-out Diameter - 170
CONSTRUCTION	Construction - Aluminium Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP40 (IP20 from above)
WATTAGE (W)	15 / 20 / 25
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1675/1750/1770/2180/2325/2335/3085/3305/3290
LUMENS LIGHT SOURCE ONLY (LM)	4060
LUMEN TOLERANCE	10%
EFFICACY (LM/W)	168.56
CIRCUIT WATTAGE (W)	24.11
CCT	3000/4000/5000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.111
DISPLACEMENT FACTOR	>0.9
SVM	0.021
PST-LM	0.59

BEAM ANGLE (DEGREES)	110
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
EMERGENCY CONVERSION KIT	EMKIT2
IC RATED	No
OPERATING TEMPERATURE	-25~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 45W OUTPUT VOLTAGE - 25-70V OUTPUT CURRENT - 350/500/600/700/800/900/1050mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270846362

Date Created: 19/08/2024 15:30

