Xnightsbridge


DATASHEET



SER3040

SEREN 230V IP40 LED Recessed Tri-Wattage and CCT Downlight - 30/ 35/ 40W

www.mlaccessories.co.uk



| MLA PART CODE | SER3040 |
|-------------------------------|---|
| DESCRIPTION | SEREN 230V IP40 LED Recessed Tri-Wattage and CCT Downlight - 30/ 35/ 40W |
| NET WEIGHT (KG) | 1.02 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 220 Recessed Depth - 69.5 Minimum Void - 100 |
| CUT-OUT (MM) | Cut-out Diameter - 200 |
| CONSTRUCTION | Construction - Aluminium Construction 2 - & polycarbonate |
| CLASS | II |
| IP RATING | IP40 (IP20 from above) |
| WATTAGE (W) | 30 / 35 / 40 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 3665/3460/3600/4275/4230/4130/4710/4745/4900 |
| LUMENS LIGHT SOURCE ONLY (LM) | 6510 |
| LUMEN TOLERANCE | 10% |
| EFFICACY (LM/W) | 179.7 |
| CIRCUIT WATTAGE (W) | 36.23 |
| ССТ | 3000/4000/5000K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.166 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0.01 |
| PST-LM | 0.575 |





Xnightsbridge

| BEAM ANGLE (DEGREES) | 110 |
|--|---------------|
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | No |
| EMERGENCY CONVERSION KIT | EMKIT2 |
| IC RATED | No |
| OPERATING TEMPERATURE | -25~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270843811 |

Date Created: 19/08/2024 15:30





