Xnightsbridge

DATASHEET



SF8900AT

Screwless 115V/230V Dual Voltage Shaver Socket - Anthracite

www.mlaccessories.co.uk

DESCRIPTION Screwless 115V/230V Dual Voltage Shaver Socket - Anthra NET WEIGHT (KG) FINISH Anthracite INSERT COLOUR Black Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP41 INPUT VOLTAGE SECONDARY VOLTAGE 115/230V	
FINISH INSERT COLOUR Black Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP RATING INPUT VOLTAGE Anthracite CHASS I I I I I I I I I I I I I I I I I I I	cite
INSERT COLOUR Black Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP41 INPUT VOLTAGE	
DIMENSIONS (MM) Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - Premium grade steel CLASS I IPRATING IP41 INPUT VOLTAGE A Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 47mm Construction - Premium grade steel I IP41	
DIMENSIONS (MM) Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - Premium grade steel CLASS I IPRATING IP41 INPUT VOLTAGE 230V 50Hz	
CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50Hz	
CLASS I IPATING IP41 INPUT VOLTAGE 230V 50Hz	
IP RATINGIP41INPUT VOLTAGE230V 50Hz	
INPUT VOLTAGE 230V 50Hz	
SECONDARY VOLTAGE 115/230V	
EARTH TERMINAL Yes	
LOAD/MAX. LOAD 20VA	
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm²	
WARRANTY 25year(s)	
MANUFACTURED IN ACCORDANCE WITH BS EN 61558-2-5	
ORIGIN OF MANUFACTURE China	
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	
EAN 5056270819052	

Date Created: 03/04/2023 13:35





