Knightsbridge

DATASHEET



SFTS1BC

230V 1G 1-way Touchless Switch - Brushed Chrome

www.mlaccessories.co.uk

DESCRIPTION230V 1G 1-way Touchless Switch - Brushed ChromeNET WEIGHT (KG)0.175FINISHBrushed ChromeDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²ADDITIONAL FEATURESRequires a neutral	
FINISHBrushed ChromeDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	ome
DIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
DIMENSIONS (MM)Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
CLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
IP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEDTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
SWITCH TYPESingle PoleSWITCH FUNCTION1-WayLOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
SWITCH FUNCTION 1-Way LOAD/MAX. LOAD 500W Resistive, 200W Inductive, 100W LED TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm²	
LOAD/MAX. LOAD500W Resistive, 200W Inductive, 100W LEETERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²	
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm²	
ADDITIONAL FEATURES Requires a neutral	
FUNCTION Touchless switch	
SENSOR TYPE PIR	
SENSOR OVERRIDE No	
OPTIMUM DETECTION RANGE (M) up to 3cm	
WARRANTY 2year(s)	
ORIGIN OF MANUFACTURE China	
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	
EAN 5056270866384	

Date Created: 03/04/2023 13:44

ACCESSORIES LTD



