
Xnightsbridge

DATASHEET




SH18ATS

230V 18W CCT Adjustable LED Gear Tray with

Sensor

www.mlaccessories.co.uk



MLA PART CODE	SH18ATS
DESCRIPTION	230V 18W CCT Adjustable LED Gear Tray with Sensor
NET WEIGHT (KG)	0.35
FINISH	White
DIMENSIONS (MM)	Height - 262 Width - 262
CONSTRUCTION	Construction - CEM-1
CLASS	I
IP RATING	IP20
WATTAGE (W)	18
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	2960
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	153.2
CIRCUIT WATTAGE (W)	19.3
ССТ	3000/4000/6000K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.09
DISPLACEMENT FACTOR	>0.7
SVM	0.003
PST-LM	0.08
BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz





Xnightsbridge

DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 21W OUTPUT VOLTAGE - 28-42V OUTPUT CURRENT - 500mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 86 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
SENSOR TYPE	Microwave
SENSOR DETECTION ANGLE (DEGREES)	150
OPTIMUM DETECTION RANGE (M)	4-7m @ 3m height
SENSOR DURATION	5sec - 30min
SENSOR LUX SETTINGS	2-50lx/Disable
STANDBY POWER	0.035W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270867947

Date Created: 03/04/2023 13:46





