## Knightsbridge


## DATASHEET



## SHE1GEMS

230V IP65 18W LED Round Bulkhead CCT with Emergency & Microwave Sensor

www.mlaccessories.co.uk



| MLA PART CODE                 | SHE1GEMS   |
|-------------------------------|--|
| DESCRIPTION                   | 230V IP65 18W LED Round Bulkhead CCT with Emergency &<br>Microwave Sensor Grey |
| NET WEIGHT (KG)               | 2.515  |
| FINISH                        | Grey   |
| DIFFUSER                      | Opal   |
| DIMENSIONS (MM)               | Diameter - 360<br>Projection - 92  |
| CONSTRUCTION                  | Construction - Die-cast aluminium  |
| CLASS                         | I  |
| IP RATING                     | IP65   |
| IK RATING                     | IK10   |
| WATTAGE (W)                   | 18   |
| LAMP TECHNOLOGY               | SMD LED  |
| LUMENS (LM)                   | 1680/1790/1810   |
| LUMENS LIGHT SOURCE ONLY (LM) | 3000   |
| LUMEN TOLERANCE               | 5%   |
| EFFICACY (LM/W)               | 132.6  |
| LUMENS EMERGENCY MODE (LM)    | 190/200/190  |
| CIRCUIT WATTAGE (W)           | 22.6   |
| сст                           | 3000/4000/6000K  |
| CRI                           | >85  |
| SDCM                          | <6   |
| RUNNING CURRENT (A)           | 0.11   |
| DISPLACEMENT FACTOR           | >0.7   |
| SVM                           | 0.006  |
| PST-LM                        | 0.112  |
| BEAM ANGLE (DEGREES)          | 110  |
| LIFE SPAN (HRS)               | 50,000   |
| L70B50 LIFESPAN (HRS)         | 50,000   |





## Knightsbridge

| LED COMPATIBLE                           | Yes   |
|--|---|
| DIMMABLE                                 | No  |
| EMERGENCY                                | Maintained / Non-maintained / Switched  |
| OPERATING TEMPERATURE                    | -20~50°C  |
| INPUT VOLTAGE                            | 230V 50Hz   |
| CABLE ENTRY (MM)                         | 20  |
| CABLE GLAND INCLUDED                     | Blind grommet   |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 21W<br>OUTPUT VOLTAGE - 28-42V<br>OUTPUT CURRENT - 500mA<br>POWER FACTOR - 0.95<br>EFFICIENCY FULL LOAD - 86<br>ISOLATION - SELV<br>AMBIENT TEMPERATURE (Ta) - 50°C<br>CASE TEMPERATURE (Tc) - 90°C |
| SENSOR TYPE                              | Microwave   |
| SENSOR DETECTION ANGLE (DEGREES)         | 150   |
| OPTIMUM DETECTION RANGE (M)              | 4-7m @ 3m height  |
| SENSOR DURATION                          | 5sec - 30min  |
| SENSOR LUX SETTINGS                      | 2-50lx/Disable  |
| BATTERY INCLUDED                         | Yes   |
| STANDBY POWER                            | 0.035W  |
| WARRANTY                                 | 5year(s)  |
| WARRANTY INFORMATION                     | Excluding battery   |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598   |
| ORIGIN OF MANUFACTURE                    | China   |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes   |
| EAN                                      | 5055832994640   |
| Date Created: 03/04/2023 13:19           |   |

Date Created: 03/04/2023 13:19





