## **X**nightsbridge

## **DATASHEET**



## SKR003A

13A 1G Recess Switched Socket with Dual USB Charger (2.4A) - Stainless Steel with black insert

www.mlaccessories.co.uk

FINISH  INSERT COLOUR  Black  Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  CUT-OUT (MM)  CUT-OUT (MM)  CUT-OUT Diameter - 112  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79 Construction - Premium grade steel  Cut-out Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  Cut-out Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  Construction - Premium grade steel  Sonstruction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I	MLA PART CODE	SKR003A
FINISH  INSERT COLOUR  Black  Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  CUT-OUT (MM)  CUT-OUT (MM)  CUT-OUT Diameter - 112  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79 Construction - Premium grade steel  Cut-out Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  Cut-out Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  Construction - Premium grade steel  Sonstruction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I Height - 85 Recessed Depth - 79  Cut-out Diameter - 112  Construction - Premium grade steel  1 I	DESCRIPTION	
INSERT COLOUR  Black  Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  CUT-OUT (MM)  Cut-out Diameter - 112  CONSTRUCTION  Construction - Premium grade steel  CLASS  I  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  NO. OF TYPE-A PORTS  2  USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	NET WEIGHT (KG)	0.8
Diameter - 120 Projection - 6 Overall Height - 85 Recessed Depth - 79  CUT-OUT (MM)  Cut-out Diameter - 112  CONSTRUCTION  Construction - Premium grade steel  CLASS  I IP RATING  IP20 INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2 NO. OF TYPE-A PORTS  2 USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	FINISH	Stainless Steel
DIMENSIONS (MM)  Projection - 6 Overall Height - 85 Recessed Depth - 79  CUT-OUT (MM)  Cut-out Diameter - 112  CONSTRUCTION  Construction - Premium grade steel  CLASS  I IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  NO. OF TYPE-A PORTS  2  USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	INSERT COLOUR	Black
CONSTRUCTION  Construction - Premium grade steel  I IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  NO. OF TYPE-A PORTS  USB CHARGING  ADDITIONAL FEATURES  CABLE LENGTH (M)  Construction - Premium grade steel  I Son Type  Provided Steel  I IP20  Single Pole  Single Pole  Single Pole  Single Pole  Single Pole  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	DIMENSIONS (MM)	Projection - 6 Overall Height - 85
CLASS I PRATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole LOAD/MAX. LOAD 13A NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING ADDITIONAL FEATURES Fitted with 2m cable length with BS Plug Top CABLE LENGTH (M)  1  1  1  1  1  1  1  1  1  1  1  1  1	CUT-OUT (MM)	Cut-out Diameter - 112
IP RATING INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole LOAD/MAX. LOAD 13A NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 2 USB CHARGING 5V DC 2.4A (shared) ADDITIONAL FEATURES Fitted with 2m cable length with BS Plug Top CABLE LENGTH (M) 2	CONSTRUCTION	Construction - Premium grade steel
INPUT VOLTAGE  SWITCH TYPE  Single Pole  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  NO. OF TYPE-A PORTS  2  USB CHARGING  5V DC 2.4A (shared)  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	CLASS	I
SWITCH TYPE  LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  NO. OF TYPE-A PORTS  2  USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	IP RATING	IP20
LOAD/MAX. LOAD  13A  NO. OF USB PORTS  2  NO. OF TYPE-A PORTS  2  USB CHARGING  5V DC 2.4A (shared)  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	INPUT VOLTAGE	230V 50Hz
NO. OF USB PORTS  2 NO. OF TYPE-A PORTS  2 USB CHARGING  5V DC 2.4A (shared)  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	SWITCH TYPE	Single Pole
NO. OF TYPE-A PORTS  USB CHARGING  ADDITIONAL FEATURES  Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2  2  5V DC 2.4A (shared)  Fitted with 2m cable length with BS Plug Top	LOAD/MAX. LOAD	13A
USB CHARGING 5V DC 2.4A (shared)  ADDITIONAL FEATURES Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M) 2	NO. OF USB PORTS	2
ADDITIONAL FEATURES Fitted with 2m cable length with BS Plug Top  CABLE LENGTH (M)  2	NO. OF TYPE-A PORTS	2
CABLE LENGTH (M) 2	USB CHARGING	5V DC 2.4A (shared)
	ADDITIONAL FEATURES	Fitted with 2m cable length with BS Plug Top
	CABLE LENGTH (M)	2
WARRANTY 2year(s)	WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH BS 1363-2, BS EN 62368-1	MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, BS EN 62368-1
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832986898	EAN	5055832986898

Date Created: 03/04/2023 13:15



