


DATASHEET



TORCDA6

230V IP65 IK08 6ft 65W DALI CCT Adjustable Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCDA6
DESCRIPTION	230V IP65 IK08 6ft 65W DALI CCT Adjustable Non-Corrosive
NET WEIGHT (KG)	2.61
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1828 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	65
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	8900
LUMENS LIGHT SOURCE ONLY (LM)	10100
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	140
CIRCUIT WATTAGE (W)	64
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.29
DISPLACEMENT FACTOR	>0.9
SVM	0.022
PST-LM	0.034
BEAM ANGLE (DEGREES)	150
LIFE SPAN (HRS)	50,000

L70B50 LIFESPAN (HRS)	60000
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - DALI MAX. OUTPUT - 84W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - 1550mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 89.5 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
STANDBY POWER	0.5W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851748

Date Created: 16/10/2023 14:58

