


DATASHEET



TORCW2

230V IP65 IK08 2ft Selectable 14W/26W CCT Adjustable Non-Corrosive

www.mlaccessories.co.uk



| MLA PART CODE | TORCW2 |
|-------------------------------|--|
| DESCRIPTION | 230V IP65 IK08 2ft Selectable 14W/26W CCT Adjustable Non-Corrosive |
| NET WEIGHT (KG) | 1.16 |
| FINISH | Grey |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 653 Width - 129 Projection - 90 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | I |
| IP RATING | IP65 |
| IK RATING | IK08 |
| WATTAGE (W) | 14/26 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1925/2100/2085, 3215/3955/3500 |
| LUMENS LIGHT SOURCE ONLY (LM) | 4465 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 169.9 |
| CIRCUIT WATTAGE (W) | 13.6/26.2 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.118 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.018 |
| PST-LM | 0.039 |
| BEAM ANGLE (DEGREES) | 130 |

| | |
|--|--|
| LIFE SPAN (HRS) | 50,000 |
| L70B50 LIFESPAN (HRS) | 60000 |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~40°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Compression gland |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 15/30W OUTPUT VOLTAGE - 35-49V OUTPUT CURRENT - 300/600mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.2 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270851601 |

Date Created: 03/04/2023 13:55

