
Knightsbridge



TORCW4

230V IP65 IK08 4ft Selectable 19W/37W CCT Adjustable Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCW4
DESCRIPTION	230V IP65 IK08 4ft Selectable 19W/37W CCT Adjustable Non- Corrosive
NET WEIGHT (KG)	1.63
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1263 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	19/37
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	2650/3015/2760, 4600/5550/4790
LUMENS LIGHT SOURCE ONLY (LM)	6220
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	169.3
CIRCUIT WATTAGE (W)	19.2/36.8
сст	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.162
DISPLACEMENT FACTOR	>0.9
SVM	0.022
PST-LM	0.045
BEAM ANGLE (DEGREES)	115





Knightsbridge

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18/37W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 420/840mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 92.3 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851526
Date Created: 03/04/2023 13:55	

Date Created: 03/04/2023 13:55





