



DATASHEET



TORCWEM2

230V IP65 IK08 2ft Selectable 14W/26W CCT
Adjustable Emergency Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCWEM2
DESCRIPTION	230V IP65 IK08 2ft Selectable 14W/26W CCT Adjustable Emergency Non-Corrosive
NET WEIGHT (KG)	1.5
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 653 Width - 129 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14/26
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1925/2100/2085, 3215/3955/3500
LUMENS LIGHT SOURCE ONLY (LM)	4465
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	169.9
LUMENS EMERGENCY MODE (LM)	315
CIRCUIT WATTAGE (W)	13.6/26.2
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.118
DISPLACEMENT FACTOR	>0.9
SVM	0.018
PST-LM	0.039

BEAM ANGLE (DEGREES)	130
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-5~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 15/30W OUTPUT VOLTAGE - 35-49V OUTPUT CURRENT - 300/600mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.2 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881059

Date Created: 16/10/2023 15:00

