Knightsbridge


DATASHEET



TORCWEM5

230V IP65 IK08 5ft Selectable 26W/48W CCT Adjustable Emergency Non-Corrosivo

www.mlaccessories.co.uk



26/48

MLA PART CODE	TORCWEM5
DESCRIPTION	230V IP65 IK08 5ft Selectable 26W/48W CCT Adjustable Emergency Non-Corrosive
NET WEIGHT (KG)	2.35
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	26/48
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3810/4045/4030, 6230/7250/6800
LUMENS LIGHT SOURCE ONLY (LM)	8085
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	167.5
LUMENS EMERGENCY MODE (LM)	320
CIRCUIT WATTAGE (W)	25.6/48.4
ССТ	3000/4000/5700K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.214
DISPLACEMENT FACTOR	>0.9
SVM	0.019
PST-LM	0.044





Xnightsbridge

140
50,000
60000
No
Maintained / Non-maintained / Switched
-5~40°C
230V 50Hz
20
Compression gland
DRIVER TYPE - Constant Current MAX. OUTPUT - 24/47W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 540/1080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.7 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C
Yes
5year(s)
(excluding battery)
BS EN 60598
China
Yes
5056270881127

Date Created: 16/10/2023 15:00





