



## DATASHEET



### TORCWM5

230V IP65 IK08 5ft Selectable 26W/48W CCT  
Adjustable Microwave Non-Corrosive

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	TORCWM5
DESCRIPTION	230V IP65 IK08 5ft Selectable 26W/48W CCT Adjustable Microwave Non-Corrosive
NET WEIGHT (KG)	2.07
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	26/48
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3810/4045/4030, 6230/7250/6800
LUMENS LIGHT SOURCE ONLY (LM)	8085
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	167.5
CIRCUIT WATTAGE (W)	25.6/48.4
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.214
DISPLACEMENT FACTOR	>0.9
SVM	0.019
PST-LM	0.044
BEAM ANGLE (DEGREES)	140

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 24/47W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 540/1080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.7 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	360
OPTIMUM DETECTION RANGE (M)	6
SENSOR DURATION	10s/1min/5min/10min/15min/20min/25min/30min
SENSOR LUX SETTINGS	10/20/50/100/200/300/500/24h
STANDBY POWER	0.5W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851656

Date Created: 03/04/2023 13:55

