



DATASHEET



TORCWM6

230V IP65 IK08 6ft Selectable 30W/60W CCT
Adjustable Microwave Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCWM6
DESCRIPTION	230V IP65 IK08 6ft Selectable 30W/60W CCT Adjustable Microwave Non-Corrosive
NET WEIGHT (KG)	2.56
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1828 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	30/60
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	4300/4750/4560, 7475/8660/8040
LUMENS LIGHT SOURCE ONLY (LM)	10000
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	164.8
CIRCUIT WATTAGE (W)	30.6/60.3
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.272
DISPLACEMENT FACTOR	>0.9
SVM	0.017
PST-LM	0.028
BEAM ANGLE (DEGREES)	150

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 27/55W OUTPUT VOLTAGE - 30-41V OUTPUT CURRENT - 660/1320mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 95.2 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	360
OPTIMUM DETECTION RANGE (M)	6
SENSOR DURATION	10s/1min/5min/10min/15min/20min/25min/30min
SENSOR LUX SETTINGS	10/20/50/100/200/300/500/24h
STANDBY POWER	0.5W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851663

Date Created: 03/04/2023 13:55

