


## DATASHEET



### TPB14LEDA

230V IP44 14W LED Bulkhead with Sensor/Dimming Function 6000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	TPB14LEDA
DESCRIPTION	230V IP44 14W LED Bulkhead with Sensor/Dimming Function 6000K
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 330 Projection - 110
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP44
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1070
LUMENS LIGHT SOURCE ONLY (LM)	1490
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	74.8
CIRCUIT WATTAGE (W)	14.3
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.03
BEAM ANGLE (DEGREES)	105
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	72,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C

<b>INPUT VOLTAGE</b>	230V 50Hz
<b>DRIVER</b>	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.5 CASE TEMPERATURE (Tc) - 65°C
<b>SENSOR TYPE</b>	Microwave - Corridor Function
<b>OPTIMUM DETECTION RANGE (M)</b>	2m~8m @ 2.5m height
<b>SENSOR DURATION</b>	10sec - 12min
<b>SENSOR LUX SETTINGS</b>	10lx - daylight
<b>STANDBY POWER</b>	0.17W
<b>WARRANTY</b>	3year(s)
<b>MANUFACTURED IN ACCORDANCE WITH</b>	BS EN 60598
<b>ORIGIN OF MANUFACTURE</b>	China
<b>DECLARATION OF CONFORMITY (HELD ON FILE)</b>	Yes
<b>EAN</b>	5055832944829

Date Created: 03/04/2023 12:55

