Knightsbridge

DATASHEET



TPB28WPEMHF

IP44 28W HF Emergency Polo Bulkhead with Prismatic Diffuser and White Base

www.mlaccessories.co.uk

DESCRIPTIONIP44 28W HF Emergency Polo Bulkhead with Prismatic Diffuser and White BaseNET WEIGHT (KG)2.002FINISHWhiteDIFFUSERPrismaticDIMENSIONS (MM)Diameter - 330 Projection - 110CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP44WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LECOMPATIBLENoDIMMABLENoDIMMABLENoEMERGENCYMaintained / Non-maintained / Switched	MLA PART CODE	TPB28WPEMHF
FINISHWhiteDIFFUSERPrismaticDIMENSIONS (MM)Diameter - 330 Projection - 110CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP44WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LIED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Non-maintained / Switched	DESCRIPTION	IP44 28W HF Emergency Polo Bulkhead with Prismatic Diffuser and White Base
DIFFUSERPrismaticDIMENSIONS (MM)Diameter - 330 Projection - 110CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP44WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)34.64LUMENS (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<66RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Non-maintained / Switched	NET WEIGHT (KG)	2.002
DIMENSIONS (MM)Diameter - 330 Projection - 110CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP44WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Non-maintained / Switched	FINISH	White
DIMENSIONS (MM)Projection - 110CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP44WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	DIFFUSER	Prismatic
CLASSIIP RATINGIP44WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Non-maintained / Switched	DIMENSIONS (MM)	
IP RATINGIP44WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMENS (LM)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1DIMMABLENoEMERGENCYNoEMERGENCYMaintained / Switched	CONSTRUCTION	Construction - Polycarbonate
WATTAGE (W)28MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6	CLASS	I
MAX. WATTAGE (W)28LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	IP RATING	IP44
LAMP TECHNOLOGYFluorescentLAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	WATTAGE (W)	28
LAMP BASE2D 28W 4PLAMP INCLUDEDYesLUMENS (LM)865LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	MAX. WATTAGE (W)	28
LAMP INCLUDEDYesLUMENS (LM)865LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	LAMP TECHNOLOGY	Fluorescent
LUMENS (LM)865LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	LAMP BASE	2D 28W 4P
LUMEN TOLERANCE5%EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	LAMP INCLUDED	Yes
EFFICACY (LM/W)34.64LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	LUMENS (LM)	865
LUMENS EMERGENCY MODE (LM)190CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	LUMEN TOLERANCE	5%
CIRCUIT WATTAGE (W)25CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6	EFFICACY (LM/W)	34.64
CCT3500KLIGHT COLOURWhiteCRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Switched	LUMENS EMERGENCY MODE (LM)	190
LIGHT COLOUR White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.1 LED COMPATIBLE No DIMMABLE No EMERGENCY Maintained / Non-maintained / Switched	CIRCUIT WATTAGE (W)	25
CRI>80SDCM<6RUNNING CURRENT (A)0.1LED COMPATIBLENoDIMMABLENoEMERGENCYMaintained / Non-maintained / Switched	ССТ	3500K
SDCM<6	LIGHT COLOUR	White
RUNNING CURRENT (A) 0.1 LED COMPATIBLE No DIMMABLE No EMERGENCY Maintained / Non-maintained / Switched	CRI	>80
LED COMPATIBLE No DIMMABLE No EMERGENCY Maintained / Non-maintained / Switched	SDCM	<6
DIMMABLE No EMERGENCY Maintained / Non-maintained / Switched	RUNNING CURRENT (A)	0.1
EMERGENCY Maintained / Non-maintained / Switched		No
	DIMMABLE	No
INPUT VOLTAGE 230V 50Hz	EMERGENCY	Maintained / Non-maintained / Switched
	INPUT VOLTAGE	230V 50Hz





Knightsbridge

BATTERY INCLUDED	Yes
WARRANTY	1year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055559112396

Date Created: 03/04/2023 14:17





