


DATASHEET



TPR14LED

230V IP65 14W LED Bulkhead 4000K

www.mlaccessories.co.uk



MLA PART CODE	TPR14LED
DESCRIPTION	230V IP65 14W LED Bulkhead 4000K
NET WEIGHT (KG)	0.55
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 285 Projection - 86
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1100
LUMENS LIGHT SOURCE ONLY (LM)	1475
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	105.4
CIRCUIT WATTAGE (W)	14
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.027
BEAM ANGLE (DEGREES)	115
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	60,000

DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 83.6 CASE TEMPERATURE (Tc) - 50°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832936930

Date Created: 03/04/2023 12:53

