


DATASHEET



TRLED151EM

110V IP65 5ft 29W SINGLE LED Non-Corrosive
Emergency- 4000K

www.mlaccessories.co.uk



MLA PART CODE	TRLED151EM
DESCRIPTION	110V IP65 5ft 29W SINGLE LED Non-Corrosive Emergency-4000K
NET WEIGHT (KG)	2.6
FINISH	Yellow
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 94
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	29
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3400
LUMENS LIGHT SOURCE ONLY (LM)	4020
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	142.19
LUMENS EMERGENCY MODE (LM)	785
CIRCUIT WATTAGE (W)	28.3
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.260
DISPLACEMENT FACTOR	>0.9
SVM	0.792
PST-LM	0.069
BEAM ANGLE (DEGREES)	120

LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	110/230V
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W EFFICIENCY FULL LOAD - 90.33% ISOLATION - SELV
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832991557

Date Created: 03/04/2023 13:18

