


DATASHEET



TRLED26EM

230V IP65 6ft 69W Twin LED Non-Corrosive Emergency

www.mlaccessories.co.uk



MLA PART CODE	TRLED26EM
DESCRIPTION	230V IP65 6ft 69W Twin LED Non-Corrosive Emergency
NET WEIGHT (KG)	4.06
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1828 Height - 90 Width - 129
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	69
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	7770
LUMENS LIGHT SOURCE ONLY (LM)	9560
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	142.76
LUMENS EMERGENCY MODE (LM)	786
CIRCUIT WATTAGE (W)	66.99
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.309
DISPLACEMENT FACTOR	>0.9
SVM	0.841
PST-LM	0.031
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000

L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 2 x 36W EFFICIENCY FULL LOAD - 89.88% ISOLATION - SELV
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832971207

Date Created: 03/04/2023 13:07

