



## DATASHEET



### TRLED26EMD

230V IP65 6ft 69W Twin LED Non-Corrosive  
Emergency - 6000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	TRLED26EMD
DESCRIPTION	230V IP65 6ft 69W Twin LED Non-Corrosive Emergency - 6000K
NET WEIGHT (KG)	4.06
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1828 Height - 90 Width - 129
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	69
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	7820
LUMENS LIGHT SOURCE ONLY (LM)	9510
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	144.50
LUMENS EMERGENCY MODE (LM)	708
CIRCUIT WATTAGE (W)	65.84
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.304
DISPLACEMENT FACTOR	>0.9
SVM	0.795
PST-LM	0.032
BEAM ANGLE (DEGREES)	120

LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 2 x 36W EFFICIENCY FULL LOAD - 89.88% ISOLATION - SELV
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832988700

Date Created: 03/04/2023 13:16

